



- Card based controller for access control and time attendance system.
- Work as standalone system or link to software via TCP/IP or RS485 connection.
- Support both card and password verification mode.
- Built-in web server for real-time control export of logs data and online check logs.
- Support real time log PUSH methodology.
- Configurable Event Handle and short message service alert thru email.
- Designed with auto obtain TCP/IP (DHCP) to simplifies network connection setup.
- Available in Mifare format.
- Ideal for various environments such as offices, factories, educational institutions and residential complexes.

Specification

Verification Mode	Card / Password	Time Set/Time Zone/Group	255/120/255 Sets
Capacity	60,000 Users	Door Opening Time	0-65535 seconds
Log Data	30,000	LCD Display	Yes
System Log	1,536	LED Indication	Blue / Green / Red LED
DIO Support	DI: 3 / DO: 1	Touch Keypad	Yes
Communication Interface	Wiegand, TCP/IP	Operation Temperature	0°C - 55°C
WG In & Out	26 or 34 bits	Operation Humidity	5% - 80% RH
Holiday/Fast Register	Yes/Yes	Power	DC 9-24V, 1A
Function Key	400 (Auto/Manual)	Weight	250g
Anti-Pass Back/Anti Duress	Yes/Yes	Dimension	144 x 80 x 18.35 mm

Layout Diagram

