

# 5005 Guard Tour System



- Super durable Silicon tank, metal body with rubber shell outside
- IP67 standard completely water proof and guard proof
- Magnetic cable design high download speed
- Non-contacting reading of RFID tag
- Big storage capacity can store up to 60,000 records
- Four color LED combines with vibration indication
- Real time internal clock
- High-capacity battery and low power consumption design one time charge for 30 days using
- Software provide different types of report that makes your management more efficient
- Sales code: MD-00GT-004-PKG

### Specification:

Physical	Metal body with rubber shell outside	
Card Format	RFID 125 KHz	
Reading Range	3-5 cm	
Communication	Magnetic USB cable, upload 15,000 records per minute	
Battery Type	3.7v Lithium recharge battery, 800m Ah	
Display	LED Status Light	
Waterproof	IP67 Completely Sealed	
Storage Capacity	16Mbit flash, 60,000 records	
Standby time	Read tags per second, can be used at least 40 hours 500 reading per day, can be used for 29 days	
Tag ID number	8 bits Hexadecimal number	
Working Temperature	-40 to 85 °C	
Working Humidity	10 to 90 %	
Dimension / Weight	114 x 47 x 30 mm / 200g	

#### Magnetic USB Communication



Magnetic USB cable can be used to connect between the reader and PC.

#### EM Proximity Token / Checkpoint



Can read and operated in wide temperature ranges.

Completely waterproof and can be sealed inside non-metalic material walls.

Working frequency: 125 KHz.

## **Event Wallet**



Event wallet are designed to hold the signal card (RFID tags) that has been pre-identified the events which usually happens during the patrol at certain checkpoints (example door open, power off,etc). The guard takes the reader and also the event wallet to begin a guard patrol.

# Battery Charging



2-3 hours each charging time. Connect the reader to charges with USB cable, the red indicator is turned on means battery is charging. When battery fully charges, red indicator will turned to green.